

# 6mm Travel Slide-linear position sensor 5mm Travel Slide-Potentiometer

## FEATURES


- Conform RoHS

## 特長

- RoHS適合品です。

Order Number	APPLICATIONS
XVJ06N4.95R-BP10K	Tele-Wide adjustment of digital camera and video camera.

## Circuit



Model	External Dimensions	Unit:mm
XVJ06N		900pcs/Reel

## SPECIFICATIONS

	XVJ06N
Operating Temperature Range 使用温度範囲	-25 to 70°C
Rated Power 定格電力	0.05W
Rated Voltage 定格電圧	AC10V, DC10V
Nominal Total Resistance 公称抵抗値	10kΩ
Total Resistance Tolerance 全抵抗値許容差	Within ±30% of the nominal total resistance
Resistance Taper 抵抗変化特性	OBP (Linear & Center Flat)
Insulation Resistance 絶縁抵抗	100MΩ min. at DC100V
Dielectric Strength 耐電圧	AC100V for 1 minute
Lever Travel レバー移動距離	6.2±0.2mm
Sliding Force しゅう動力	0.08 to 0.4N at 25±5°C
Sliding Life 耐久性 (しゅう動)	10,000cycles

- Specifications in this catalog are presented basically for informative purposes. We request the exchange of official approval drawings before placing order.
- 当カタログは参考仕様ですので、ご使用にあたっては正式納入仕様書の取り交わしをお願いします。